

ES5-12FR

Maintenance-Free Rechargeable Sealed Lead-Acid Battery

Nominal Voltage (V) 12V

Capacity 25°C (77°F)

20hour rate @ 0.25A	5.0Ah
5 hour rate @ 0.8A	4.0Ah
1 hour rate @ 3.0A	3.0Ah
1 C @ 5.0A	2.5Ah

Weight 4.03 Lbs. (1.83 kg)

Internal Resistance (25°C, 77°F) ~32 mΩ

Maximum Discharge Current for 5 seconds : 60A

Maximum Charge Current (A) 1.5A

Discharge Capacity under Different Temperatures

40°C	: ~102%
25°C	: ~100%
0°C	: ~85%

Charging Methods at 25°C (77°F)

Cycle use:

Charging Voltage 14.7 ± V0.3V

Standby use:

Charging Voltage 13.65 ± V0.15V

Self-Discharge Residual Capacity (25°C, 77°F)


After 3 months	: ~90%
After 6 months	: ~82%
After 12 months	: ~70%

Case Material UL94V-0 ABS

Terminal F1




Dimensions



Tolerances are +/-0.04 in. (+/-1mm) and +/-0.08 in. (+/-2mm) for height dimensions.

Discharge Current vs Time



MK Battery
 1645 South Sinclair Street • Anaheim, California 92806
 Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-Mail: sales@mkbattery.com

