

# DC245-6 DATA SHEET



## DC245-6

245AH@20HR

6-Volt

DEEP CYCLE

Maintenance-Free  
Sealed AGM Battery

### Nominal Specifications

Battery Model	DC245-6	Rated Capacity	245AH/20HR
---------------	---------	----------------	------------

### Mechanical Specifications

Group Size	DIN	
Overall Height (H)	275±2mm	10.83"
Container Height (h)	275±2mm	10.83"
Length	244±2mm	9.61"
Width	190±2mm	7.48"
Weight	Approx.32.6kg	71.87lbs.
Terminal Type	AP-Auto Post Terminal	
Terminal Torque	5.6-7.9N.m	
Container Material	ABS Standard UL 94-HB	

### Electrical Specifications

C100	270AH
C20	245AH
C10	221AH
C5	198AH
CCA	1105A
CA or MCA	1320A
HPCA	1590A
Max. Discharge Current	2450A (5s)
Internal Resistance	1.2mΩ
Reserve Capacity	
Reserve @25 AMPS	457Minutes
Reserve @75 AMPS	120Minutes




### Temperature Range Specifications

Operating Temperature Range	Discharge: -15 ~ +50 (5 ~ 122 °)
	Charge: -15 ~ +40 (5 ~ 104 °)
	Storage: -15 ~ +40 (5 ~ 104 °)
Recommended Operating Temperature Range	+74 °(23 °) to +80 °(27 °)
Self-Discharge	Less than 10% after 90 days, can be stored up to 6 months at 25 (77 °); Fully recharging is required before usage, For higher temperatures the time interval will be shorter.

### Charge Voltages


Float Charging Voltage	6.75 to 6.90 VDC/unit @ (25°C)	
Equalization and Cycle Service Charging Voltage	7.15 to 7.25 VDC/unit @ (25°C)	
Maximum Charge Current(A)	61.2A	
Charging Temperature Compensation	Cycle use	-4mV/cell/
	Float use	-3mV/cell/

### BATTERY & TERMINAL DIMENSIONS (All units shown in mm)



Battery bank spacing required 12.5mm (1/2"inch) minimum

Terminal: AP-Auto post Terminal



### Constant Current Discharge Rating Amperes @ 77 °(25 °)


Cut off voltage V/cell	15M	30M	45M	1H	2H	3H	5H	8H	10H	12H	20H
1.75V	360	217.8	163.3	137.1	74.9	55.4	38.9	26.7	22.1	18.8	12.3

Note The above data are average values, and can be obtained with 3 charge/discharge cycles. These are not minimum values.




# DC245-6 DATA SHEET


## Terminal Voltage(V) and Discharge Time




## Duration of discharge vs. Discharge current




## Percent Capacity vs. Temperature



## State of Charge(SOC) vs Open Circuit Voltage(OCV)



## Capacity Retention Characteristic



## Cycle Life vs. Depth of Discharge(DOD)

