



# ES1.2-6

## SPECIFICATIONS

Nominal Voltage (V) 6V

### Nominal Capacity

20 hour rate ( 0.06A to 5.25V )	1.2Ah
10 hour rate ( 0.114A to 5.25V )	1.14Ah
5 hour rate ( 0.204A to 5.1V )	1.02Ah
1C ( 1.2A to 4.80V )	0.68Ah
3C ( 3.6A to 4.80V )	0.48Ah

Weight Approx. 0.65Lbs. (0.30kg)

Internal Resistance (at 1KHz) Approx. 41 mΩ

Maximum Discharge Current for 5 seconds : 18A

### Operating Temperature Range

Charge	-15°C ( 5°F ) to 40°C (104°F )
Discharge	-15°C ( 5°F ) to 50°C (122°F )
Storage	-15°C ( 5°F ) to 40°C (104°F )

### Charge Retention (shelf life) at 20°C ( 68°F )

1 month	92%
3 months	90%
6 months	80%

### Charging Methods at 25°C ( 77°F )

**Cycle Use :** Charging Voltage 7.20 to 7.50V  
Coefficient -5.0mv / °C / cell  
Maximum Charging Current : 0.36A

**Standby Use :** Float Charging Voltage 6.75 to 6.90V  
Coefficient -3.0mv / °C / cell





Case Material : ABS  
(Option : UL94 HB Flame Retardant Case Material)

Terminal : F1

## Maintenance-Free Rechargeable Sealed Lead-Acid Battery



## DIMENSIONS



## MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

